









SENSORS.NL

G231

50 I/min 0.25 kW



Switch IRON-50 with aluminium flange kit Built-in stainless filter of 350 µm Aluminium flange kit



■Optional • F1" aluminium flange kit

800003022

- · This pump is for the diesel transfer with 230 or 110 VAC connection. This pump is self-suction, eccentric with selfadjusting blades.
- It has a recirculation bypass valve. Its motor has ventilator.
- It is suitable for the agricultural, building and industrial uses.

▶ Flow curves 3-----20 30 Flow (I/min)

TECHNICAL DATA

- · Self-suction self-priming. Eccentric with self-adjusting blades
- Suction: 5 m · Delivery: 30 m
- Flow with free outlet: 50 I/min
- · Consumption: 1.2-2 A
- Motor: 0.25 kW 230 or 110 VAC 50/60 Hz single-phase, self-ventilated, dust protected
- With thermal protector
- · S1 continuous duty
- IP-55 protection
- 3,000 rpm
- Bypass Pressure: 2-2.5 bar
- Built-in stainless filter of 350 µm (micron)
- · Connection through F1" (BSP) threads and flanges
- 3 m electric cable with approved plug
- ON/OF luminous switch
- Special corrosion treatment

> KIT EQUIPE



mm | 585 620

KIT EQUIPE S-50 230 VAC **KIT EQUIPE SE-50 230 VAC**

55050-CF00000 55051-CF00000

Composed of:

- IRON-50 230 VAC pump
- MG-80 mechanical meter or MGE-110 electronic meter
- FG-100 · Transparent microfilter · 2-litre capacity · 5 μm (micron), with water decanter and drain valve
- AS-5B steel outdoors cabinet with bottom hose opening, inner nozzle hanger and locking with key and/or padlock (padlock not included)

IRON-50 0,25 kW (230 VCA)

Self-suction Diesel Pump Débit: 50 l/min

2/

➤ KITS PUMP + METER + CABINET





KIT S-50 230 VAC + AS-5P CABINET KIT SE-50 230 VAC + AS-5P CABINET 55110-CF00000 55111-CF00000

Composed of:

- IRON-50 230 VAC
- MG-80 mechanical or MGE-110 electronic meter
- AS-5P steel outdoors cabinet with nozzle hanger with microswitch to make the automatic stopping, bottom hose opening and locking with key and/or padlock (padlock not included).

S-50 230 VAC · PUMP WITH LITRE METER

- · Kit composed of pump with mechanical or electronic meter
- · It can be assembled on a metallic base.


S-50 230 V with metallic base no. 4







Connection of the meter to the pump through a long flange.



31594-CF00000 30702-CF00000 31612-CF00000 30713-CF00000



Optional

- *M1" flange kit with long union in PA + Fibreglass
- Stainless filter-sieve of 350 µm (micron) Ø33 mm
- FUP-1 FF1" filter of 350 µm (micron)

800003027 460000003 66030

The horizontal kits are equipped with:

- IRON-50 230 VCA pump (with or without meter)
- Manual or automatic nozzle
- *Accessories:
 - 4 m antistatic diesel delivery hose Ø3/4" mm double layer, with adapters on both ends
 - 1.70 m diesel hose Ø25 mm
 - M1" x 25PP adapter
 - 2 brackets 25 x 40
 - PP lower filter



Pump	Accessories	Meter		Nozzle		
	*		000	T.	O	
IRON-50 230 VAC		MG-80 Mechanical	MGE-110 Electronic	PSF-040 Manual	PA-60 Automatic (Swivel included)	
•	•			•		16
•	•				•	16
•	•	•		•		16
•	•	•			•	16
•	•		•	•		16
•	•		•		•	16

16000-CF00000 16000-CF00001 16001-CF00000 16001-CF00001 16002-CF00000 16002-CF000001

▶ VERTICAL KITS WITH TELESCOPIC TUBE AND IRON-50 230 V PUMP

The vertical kits are equipped with:

- IRON-50 230 VCA pump (with or without meter)
- Manual or automatic nozzle
- *Accessories:
 - 4 m antistatic diesel delivery hose Ø3/4" mm double layer, with adapters on both ends
 - M1" F1 1/4" telescopic tube kit, height 1.90 m with filter built in
 - MF1" brass elbow



Pump	Accessories	Meter		Nozzle		
	*	-	000	ST.	D	
IRON-50 230 VAC		MG-80 Mechanical	MGE-110 Electronic	PSF-040 Manual	PA-60 Automatic (Swivel included)	
•	•			•		16003-CF00000
•	•				•	16003-CF00001
•	•	•		•		16004-CF00000
•	•	•			•	16004-CF00001
•	•		•	•		16005-CF00000
•	•		•		•	16005-CF00001

^{*} Without filter